




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 39/04		A2	(11) International Publication Number: WO 99/59672
			(43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/US99/11146		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 20 May 1999 (20.05.99)		<p>Published Without international search report and to be republished upon receipt of that report.</p>	
(30) Priority Data: 09/081,728 20 May 1998 (20.05.98) US			
(71) Applicant: BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US).			
(72) Inventors: JEPSON, Steven, C.; 103 S. Cedar Street, Palatine, IL 60067 (US). DUDAR, Thomas, E.; 228 North Crescent, Palatine, IL 60067 (US). MONTANEZ, Rodrigo, A.; Apartment 1514, 1390 South White Oak Drive, Waukegan, IL 60085 (US). BINDOKAS, Algirdas, J.; 67 Waverly, Clarendon Hills, IL 60514 (US). FINLEY, Michael, J.; 30617 East 113th Street, Wilmot, WI 53192-0084 (US). WHITE, Jason, J.; 7936 South Calumet, Chicago, IL 60619 (US). SUMMERS, Camille; 39963 N. Hidden Bunker Court, Antioch, IL 60002 (US). DING, Y., Samuel; 302 Richmond Lane, Vernon Hills, IL 60061 (US). DANIELS, Lewis, E.; 5018 W. Lake Shore Drive, Wonder Lake, IL 60097 (US).			
(74) Agents: NICHOLS, Jeffrey, C. et al.; Baxter International Inc., One Baxter Parkway, Deerfield, IL 60015 (US).			

(54) Title: NEEDLELESS CONNECTOR

(57) Abstract

A needleless connector (450) is provided which utilizes a resealable preslit septum valve (402). The valve (402) is resiliently restrained relative to a housing (418) with the valve and housing configured to accept a standard male luer lock having a luer tip (18) which penetrates the valve through the opening to extend within the housing and a luer locking flange of the luer lock extending about the housing. The valve (402) includes a disk shaped upper portion (404) covering the opening, a lower portion (406) spaced from the housing (418) and extending downward from the disk shaped portion into a passageway defined by the housing (418), and an annular skirt (408) to attach the septum to the housing. The connector (450) exhibits satisfactory leak pressure after multiple connections and disconnects to the luer lock fitting and long periods of indwell of the luer tip (18).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

NEEDLELESS CONNECTOR

Field of the Invention

The present invention relates generally to needleless fluid connection devices and more specifically to a device for repeatedly establishing a
5 sealed connection to a conduit or a container for medical applications.

Background of the Invention

One very prevalent form of health care therapy is infusion or intravenous ("I.V.") therapy whereby fluids possessing desired medication or other characteristics are infused into a patient over varying lengths of time.
10 To practice this infusion therapy frequently a connection needs to be made between components for the transfer of fluid between the two components, along a fluid passageway and eventually to a patient. As an example, administration sets are widely used to administer liquids parenterally to a patient and other medical devices are connected to the administration set to
15 provide the proper administration.

One widely used connector for making a connection between medical devices to establish a fluid passageway is a luer connection assembly. In the luer connection assembly, a male luer tip component or fitting having a frustoconical shape is inserted into a female luer component
20 or fitting having a frustoconical shaped receiving cavity and opposing conical surfaces come into contact to form a sealed friction fit.

Until the connection is made, the passageway through each of the luer fittings and into the lumen of a component attached to the luer fitting is open to the environment. This lumen and the passageway through the luer
25 connectors form a portion of the fluid passageway and must be sterile prior to use and then sealed against microbial ingress during use. Thus, these connection assemblies and the associated components are packaged in sterile packaging and the connections are typically made just prior to establishing fluid communication with a patient's venous system.

There are two general types of luer connection assemblies. One type is generally referred to as the luer slip where the connection is maintained by the friction fit between the male luer tip and female luer component. The other type is generally referred to as a luer lock connection whereby the male luer tip is encircled by an annular flange having a threaded internal surface. The female component includes a corresponding thread formed about the outer surface. Engaging the threaded flange to the threaded outside surface establishes the connection between the male luer tip and female component while preventing accidental disconnects.

To insure a universal luer connections among components provided by a multitude of manufacturers, luer connection assemblies are manufactured to comply with universal standards. Very important sets of standards such as ANSI and ISO standards. These standards includes standard dimensions for male slip and luer lock assemblies. Among these dimensional standards are standards which define the spacing or clearance between the annular locking flange and the male luer tip. Thus any female connection device configured to establish a connection to a standard male luer lock must be able to engage the luer tip and locking flange within this clearance or spacing.

Other standards in the ISO standards include several performance requirements for luer connections. One such requirement is that after a luer lock type connection is made, to prevent inadvertent disconnection, the luer connection should resist an axial removal force of 8 pounds and unscrewing torque less than 2.8 in/oz without disconnection. Luer connections should also hold a seal against 45 psi after a connection torque of 16 in/oz has been applied. In standard luer connections this resistance and sealing is supplied by the friction between the opposing conical surfaces.

Once a component of I.V. therapy is placed in fluid communication with the body, the fluid passageway should be sealed from the environment to prevent contamination and this passageway should also be sealed so as to not allow any leakage of bodily fluids into the environment. However,

most therapies require periodic access to the fluid passageway. Because the portion of the fluid passageway through a female luer connection component is open to the environment, these components will not form a sealed connection to the fluid passageway after the fluid passageway is placed in fluid communication with the body.

In one prevalent example of intravenous therapy, fluid containing a drug in solution is injected into a primary flow of fluid from an I.V. solution container through an administration set to a catheter extending within a vein. The drug containing fluid may be injected from a syringe, secondary medication set or the like, into the set where it mixes with the flowing fluid. In another prevalent example, fluid is injected directly into or withdrawn from a catheter extending within the body. In addition the catheters are flushed periodically to maintain patency by the injection of small amounts of saline or heparin.

As can be appreciated, it is highly desirable to maintain catheters and administration sets in service as long as possible without compromising the safety of the patient. Replacement of catheters and sets is time consuming and expensive. Therefore over the period of time of use of a set or catheter there may be many connections and disconnects. For example, there may be over 100 connections and disconnects to a connection site on a catheter or set before the catheter or set is replaced. In addition a connection may be made and that connection maintained for an extended period of time before disconnection. For example a connection may be made for up to seven days of "indwell" and yet the connection should still be capable of accepting intermediate and subsequent connections and disconnects without allowing leakage to the environment.

Another highly desirable attribute of a connector is the ability for such a connector to seal against pressurized fluid found within a set or for the connector to possess a certain leak pressure in excess of a desired pressure. For example it is desirable for a connector to have a leak pressure which is in excess of 20 p.s.i. for a short period of time such as when a bolus administration of drug is injected into a set and a leak

pressure in excess of 6 p.s.i. of continuous pressure during infusion of medication.

In addition, a connector may be exposed to negative pressure particularly when such connector is located upstream of an inlet of an intravenous pump. Failure to prevent aspiration through a connector when the connector is exposed to negative pressure may lead to an aspiration of air and/or microbes into the fluid passageway.

Depending on the application, many other features may be desirable. Dead spaces within any connector which cannot be "flushed" should be minimized or eliminated as they may form an environment for microbial growth. Also, priming volume for the connector should be minimized.

Because intravenous therapy is practiced on a worldwide basis and millions of connection sites are used every year and the costs of components used in such therapy are a factor in the cost of therapy, any desired connector should be capable of being manufactured at high speeds and low cost. Generally the lower the number of parts making up a component, the lower the number of molds and high speed assembly devices both of which generally translate to lower capital expenditures and therefore lower costs.

On the other hand, whatever the connector configuration, it is highly desirable that the connector be capable of low defect manufacture. Even a small number of failure is generally unacceptable when a single failure may put a patient or health care provider at risk.

Moreover, it is also highly desirable that any surfaces around an inlet into a connector be able to be swabbed or otherwise disinfected. Typically unbroken or smooth surfaces facilitate swabbing and other disinfecting techniques.

As mentioned previously, although luer connectors are widely found in the medical environment such connections are generally not acceptable when many of the above described requirements need to be satisfied. This is primarily due to the fact that the opening through the luer connector is not sealed so that upon disconnection the opening and the fluid passageway

are open to the environment which would pose a health hazard to the patient.

Another factor which prevents use of luer connection assemblies in administration sets or injection sites is the inability for such a connector to seal against the pressurized fluid found within a set unless that connector is sealed or connected to a mating connector. The opening in a luer fitting will obviously allow such a pressurized fluid to leak.

To allow the sealed connections and disconnects to a fluid passageway extending in a set or catheter, on many sets there are one or more injection sites having a solid resilient septum in a housing are placed on the set or catheter. A sharpened needle is used to penetrate the septum to provide a connection to the fluid passageway. Although such connections possess many of the desired characteristics for sealed connections, the sharpened needles poses a needlestick hazard.

To combat the needlestick hazard, one embodiment of a needleless systems has been developed which utilizes a resealable septum formed with a slit and compressed within a housing. These needleless systems performed quite well; however, the septum can not be penetrated with a male luer tip and thus a blunt cannula is utilized having a diameter smaller than a male luer tip. If the device to which a connection needs to be made has a luer connector, these blunt cannula are generally attached to the luer fitting. The requirement of the blunt cannula potentially increases the costs of using these types of connectors.

Another type of needleless systems use connectors which are constructed to establish a connection directly with the male luer tip whether such luer tip forms a part of a luer slip or a luer lock. However connections which are to be established with a male luer tip in a manner similar to a luer lock connection described above must be capable of fitting within the standard spacing between a luer tip and locking flange and should also meet other standards which have been set out for such connections.

Examples of these systems' connectors to establish a connection directly with a male luer tip are shown in US Patent no. 5,685,866, the

disclosure of which is incorporated by reference herein. These connectors appear to all possess shortcomings which hinder widespread acceptance by medical practitioners. In general, all of these devices perform in an inferior manner when measured relative to the desirable qualities for connector devices discussed above and also in comparison to the performance standards of a injection site for a sharpened needle and resilient septum or a blunt cannula and pre-slit resilient septum

For example, several connectors utilize a resilient boot or other seal which is placed within a housing and collapsed by the introduction of a male luer tip. Upon removal of the tip, such collapsing boots must then recover to reseal the connection. Many of these boots stick in the collapsed position which leads to leaking. In addition these moving parts present an interface between the movable boot and housing into which fluid may flow and collect and such collected fluids form a fertile environment for microbial growth, and recessed surfaces and gaps are hard to disinfect. Moreover, the spikes act as flow restrictors and may impart severe turbulence to fluid as it flows through the openings in the spike. Furthermore, after withdrawal of a male luer tip the boots may not recover quickly enough to seal the entrance through the connector and the fluid passageway may be briefly exposed to the environment.

One type of such luer tip connectors has a spike within the housing which penetrates a collapsing boot. The spike has openings proximate an end adjacent the boot and form an internal passageway for the flow of fluid which is opened when the spike penetrates the collapsed boot and spreads the slit. Upon recovery, any slit or opening in the boot must reseal. However, the spike design has exhibited unsatisfactory leakage after a number of connects and disconnects which does not provide for extended use of a set or catheter.

In addition, these connectors have a multitude of parts which increases manufacturing costs and opportunities for malfunction. These designs also produce a connector having voids which cannot be flushed such that stagnant fluid may collect. Moreover, several of these device

have potential passageways from voids within the housing but outside the primary fluid passageway, into the primary fluid passageway which may allow any microbial growth within the housing to enter the fluid passageway. Also the interface between the housing and boot is difficult to swab when
5 the boot is in the uncompressed position.

A device described in US Patent no. 5,616,130, the disclosure of which is incorporated by reference herein, utilizes an elongated cam to spread open a slit in a collapsing boot, and would appear to possess several of the shortcomings of the spike and boot designs described above.

10 It is generally not a problem for the boot connectors to have ends which engage the male tip and locking flange on a standard luer lock. The sealing mechanism is below the end of the luer tip when the tip is engaged to the connector, thus there is a large amount of flexibility in the configuration of the end of the connector housing which engages the male
15 luer lock.

To overcome many of these deficiencies, needleless connections which utilize a preslit septum as one of the components were developed. These connectors establish a connection with the penetration of the slit in the septum by the luer tip. One such connector is shown and described in
20 US patent number 5,578,059, the disclosure of which is incorporated by reference herein. In the disclosed valve, a resilient preslit septum is utilized to form an environmental barrier. The septum is sealingly captured or held to the housing by having a lower flange which is pinched between a retainer and housing. It appears that the radially extending portion having a slit is
25 maintained in position by the column strength of an outer axially extending cylindrical portion extending upward from the lower flange. However the septum appears not to be capable of sealing against the pressurized fluid found in a set. Thus the valve uses a second lower check type valve to seal against the pressure.

30 To satisfy ISO dimensional standards and torque removal resistance standards the outer portion of the retainer is formed with a tapered threads so that the connection to a luer lock's straight thread design is similar to a

standard NPTF/NPSI connection. The tapered thread design extends over the end of the housing that engages the threads on a male luer lock. Such a thread design may produce too rapid an increase in engaging force during the connection which may lead to a lock up of the luer lock to the connector.

5 Such a device suffers from several other drawbacks. The valve includes a number of components to make up the housing, the environmental valve and check valve, and this high number of components increases manufacturing costs. In addition, maintaining the septum in position by the column strength of the axially extending portion of the
10 septum forces that portion to have a relatively large thickness. Thus for the septum, the axially extending wall and surrounding housing to fit within the clearance between the luer tip and the locking flange upon penetration of a male luer tip to a desired depth, the housing must be thinned. Such a thinned housing may fracture upon repeated connections and disconnects.

15 A second connector is described in US patent number 5,533,708, the disclosure of which is incorporated by reference herein. This connector also utilizes a preslit septum which is supported on an axially extending column having sufficient thickness to support the septum upon introduction of the male luer tip. The further provide sufficient column strength the axially
20 extending portion is also formed with a specific tapered shape including a thickened lower portion. To seal the slit during introduction and removal of a luer tip, the underside of the pre-slit radial portion of the septum is formed with biasing ribs.

 This connector also uses a retainer which pinches a lower radial
25 flange to sealingly fix the septum to the housing. Thus the connector includes three separate pieces. In addition the thickened axially extending portion of the septum forces the retainer to be thinned such that to presumably supply strength to the retainer the stated preferred material for the retainer is metal which increases manufacturing costs. In addition it is
30 believed that such valves will not exhibit satisfactory leak pressure after long periods of indwell, likely due to compression set of the septum material

due to a perceived high level of compression of the septum material between the tip and retainer.

To supply the necessary unscrewing resistance, the retainer is tapered outward proximate the end to establish a frictional engagement with the threads on a male luer lock.

Another feature which is desired by some users, is that a connector not siphon fluid from an attached tubing or catheter into the connector upon removal of the luer tip as this may cause fluid to flow into the other end of the catheter which it is felt may lead to blockage of the tubing. In addition it is desired that a connector is provided which actually expels fluid from the connector upon removal of the luer tip and preferably expels such fluid in a controlled manner.

Therefore, it is a main object of the invention to overcome those disadvantages of the prior art which prevent widespread acceptance of needleless valves which do not require a blunt cannula.

There are other secondary objects, one or more if satisfied may promote market acceptance but satisfaction of each may not be necessary. One object of the present invention is to provide a needleless connector fitting which may be actuated by a male luer tip without using a sharpened needle or an adapter such as a blunt cannula or the like. A related object is to provide a connector which may engage a standard luer lock fitting. A further related object is to provide such a connector which may be coupled to a standard male luer lock and complies as much as possible with ISO and ANSI standards for luer connectors

Another object of the present invention is to provide a connector which possess sufficient strength to avoid cracking or fracture.

It is a further object of the present invention to provide a connector device which utilizes a minimum number of parts and therefore minimizes opportunity for malfunction.

It is another object of the present invention to provide a connector device which is capable of providing for a large number of connections and disconnects while maintaining the ability to seal against fluids under

pressures typically found in an administration set. A related object is to provide such a connector which is capable of providing a minimum of 100 connects and disconnects without compromising the performance.

It is yet a further object of the present invention to provide a
5 connector which upon a disconnection, maintains a leak pressure of 6 psi. constant pressure and 20 psi transient pressure after 4 days of indwell.

It is a further object of the present invention to provide a connector which is capable of high speed manufacturing. It is a related object of the present invention to provide a connector which may be manufactured with a
10 very low number of potential defects.

It is yet another object of the present invention to provide a connector which minimizes voids which cannot be flushed in which stagnant fluid can collect to form a media for microbial growth. It is a related object of the present invention to provide a connector which forms a sealed fluid path
15 such that a minimum number of microbes enter the fluid path during operation using aseptic techniques. It is a further related object to provide a connector which requires a low priming volume.

It is still a further object of the present invention to provide a connector which minimizes or eliminates flow restrictions for the flow of fluid
20 through the connector. In addition it is an object to provide a connector having smooth unbroken surfaces about any inlet to facilitate aseptic techniques.

It is yet another object of the present invention to provide a connector which forms a continuous closed system which seals the fluid passageway
25 from the environment during and after insertion of a male luer tip and instantaneously after withdrawal of the luer tip.

It is a further object of the present invention to provide a connector which does not siphon fluid into the connector from an attached medical device upon removal of a luer tip. A related object is to provide a connector
30 which provides a flow of fluid from the connector during and possibly after removal of the luer tip.

Summary of the Invention

The above main object is satisfied by connector utilizing a resealable valve having an opening extending through at least a portion of the valve. The valve is resiliently restrained relative to a housing with the valve and housing configured to accept a penetrating member having a tip which
5 penetrates the valve through the opening.

One or more of the secondary objects are satisfied by a valve uniquely configured to seal against pressures typically found in fluid passageways which are in fluid communication with the body. Preferably
10 the resealable valve is a septum and the septum and housing are uniquely configured to accept male luer tips. In one embodiment, the septum includes an upper generally disk shaped upper portion covering an opening defined by the housing and a portion extending downward from the upper portion with the valve opening extending through both the upper and lower
15 portion.

The upper portion of the valve is resiliently retained relative to the housing by integral attachment with an annular skirt and the skirt may be attached to the interior surface of the housing in a first embodiment and surrounding and attached to an exterior surface of the housing in a second
20 embodiment.

Brief Description of the Drawings

Figure 1 is a section view of a first embodiment of a needleless connector of the present invention;

Figure 2 is a section view of the connector of Figure 1, shown
25 connected to a male luer tip;

Figure 3 is a section view of a septum forming a part of the connector of Figure 1;

Figure 3a is a bottom plan view of a septum forming a part of the connector of Figure 1;

Figure 4 is a section view of a second embodiment of a needleless connector of the present invention;

Figure 5 is a section view of a septum forming a part of the connector of Figure 4;

5 Figure 5a is a bottom plan view of a septum forming a part of the connector of Figure 4;

Figure 6 is a perspective view of the connector of Figure 4;

Figure 7 is a sectional view of a connector similar to the connector shown in Figure 4 included as a part of a Y-site;

10 Figure 8 is a third embodiment of the needleless connector of the present invention;

Figure 9 is a section view of an alternate embodiment of a needleless connector of the present invention;

15 Figure 10 is a section view of the connector of Figure 9 shown connected to a male luer tip;

Figure 11 is a section view of a further alternate embodiment of a needleless connector of the present invention; and

Figure 12 is a section view of the connector of Figure 11 shown connected to a male luer tip;

20 Figure 13 is a section view of a further alternate embodiment of a needleless connector of the present invention;

Figure 14 is a section view of the connector of Figure 13 shown connected to a male luer tip;

25 Figure 15 is a section view of a further alternate embodiment of a needleless connector of the present invention; and

Figure 16 is a section view of the connector of Figure 15 shown connected to a male luer tip.

Detailed Description

30 The following description is not intended to limit the claimed invention to the described embodiments and the disclosed combination of features in the various embodiments might not be absolutely necessary for the inventive solution.

Referring to Figure 1, a first embodiment of a connector device of the present invention is generally indicated at 10. The connector 10 generally provides multiple fluid connections with a penetrating member 12 (Figure 2). In an example, the connector 10 may be attached to a conduit 14 in fluid
5 communication with the human body. The conduit 14 may be a peripheral catheter 15, medical tubing or the like and forming a passageway 16 in fluid communication with the body for the flow of fluid to or from a body. The connector 10 may also be attached to other devices such as a vial or vial adapter (not shown) or the like or the connector may be used in lieu of open
10 female luer fittings such as fittings on stopcocks.

Referring to Figure 2, in an example, the penetrating member 12 is preferably a male luer slip or luer lock 13 conforming to ANSI or ISO standards; however, examples of other members, with appropriate modifications to the housing and septum, may include blunt cannula,
15 needles, specially designed connectors or the like. The luer lock 13 includes a luer tip 18 which, in the embodiment shown, is encircled by a locking flange 20 and forms the end of a syringe 24. Other devices which may utilize a penetrating member 12 include I. V. sets, blood collection and peritoneal dialysis devices and the like.

Referring also to Figure 1, the connector 10 includes a housing 26
20 and an elastic and resilient resealable member 27, preferably a septum 28, disposed at an upper end 30 of the housing to seal an opening 32 defined by the upper end 30. The septum 28 is operably connected to the housing 26 with a central portion 34 elastically restrained relative to the housing
25 such that the central portion 34 may be stretched downward into the housing as the penetrating member 12 is inserted into the opening. The central portion 34 elastically retracts upon removal of the penetrating member 12. The housing 26 forms an axially extending passageway 36 which extends downward from the opening 32 and is in fluid
30 communication with the lower passageway 16 defined by the conduit 14. The resealable member 27 is uniquely configured to seal the opening 32 when the central portion 34 is in the occluding position shown in Figure 1.

The central portion 34 of the septum 28 has a generally disk shaped upper portion 38 and a lower portion 40 extending axially downward within the passageway. A resealable opening 44, such as a slit 46 extends downward preferably through both the upper portion 38 and lower portion 40. It is anticipated that the opening 44 may be formed so that initially the opening may extend only through a portion of one or both of the upper and lower portions 38, 40; however, extending a penetrating member 12 completely through the septum 28 will force the opening to also extend completely through the septum 28. Preferably the opening 44 is configured in such a manner such that when the penetrating member 12 extends completely through the septum 28 the upper and lower portions 38, 40 are elastically stretched about the penetrating member to seal against leakage through the interface between the penetrating member and the septum.

The slit length in the horizontal direction is preferably shorter than one half the circumference of the tip end of the luer tip 18.

As shown in Figure 3 and 3a, in the first embodiment, the lower portion 40 forms a generally rectangular horizontal cross section. Vertically extending sidewalls 48 and end walls 50 are slightly tapered so that the lower portion 40 forms a trapezoidal vertical cross section which facilitates molding and orienting the septum during manufacturing particularly when forming an opening 44. The opening 44 may extend straight downward or be oriented at an angle relative to the vertical. In addition, the opening 44 may be a slit 46 or may be curved or slightly helically rotated to promote the sealing of the opening.

Referring back to Figure 1, the septum 28 includes an annular skirt 52 which extends downward within the passageway 36 and is attached to the inner surface 54 of the housing 26 to elastically restrain the central portion 34 relative to the housing. The attachment is preferably made by adhesively bonding an outer surface 56 of the skirt 52 to the inner surface 54. Because displacement of the central portion 34 into the passageway 36 by the luer tip 18 (Figure 2) applies shear stress to the attachment between the skirt 52 and housing 26, the septum 28 includes a radial lip 58 which

extends over and is attached to an upper edge 60 of the housing. The attachment of the lip 58 and edge 60 at least partially supports the skirt 52 and aids in resisting the shear forces. In the first embodiment, the attachment between the lip 58 and edge 60 is by an adhesive bond in the same manner as the attachment of the housing and the skirt 52.

Referring to Figure 2, to insure universal connectivity, it is preferable that dimensions of luer connecting devices are standardized to ISO standards. For example, the dimensions of the luer tip 18 including the taper are set by the standard. Similarly threads 64 on the inside of the locking flange 20 define a clearance radius which is set by the standard. As can be appreciated, when the male luer tip 18 extends within the connector 10 and the locking flange 20 extends about the exterior of the connector, the size of the connector and its components are constrained within the spacing between the luer tip and locking flange. Also, according to ISO standards, the male luer tip 18 should be able to penetrate to a desired insertion depth "D" of .300 inches which additionally constrains the size of the connector 12 and its components particularly about the upper end 30 of the housing 26 which must fit within the spacing between the luer tip 18 and locking flange 20.

In Figure 2 the luer tip 18 is shown forcing the septum 28 into an open position. In particular the tip 18 extends through the opening 44 to the desired depth D, establishing fluid communication between a passageway 66 in the tip 18 and the passageway 36. To minimize any flow restriction, the passageway 36 adjacent the tip 12 is preferably open to the passageway 16 without any secondary valves or other obstructions to fluid flow. The upper portion 38 of the septum 28 pivotally deforms downward, stretches and extends along the annular skirt 52 and the outer surface 68 of tip. In addition the lower portion 40 of the septum 28 extends downward and stretches about the outer surface 68, and establishes a seal about the tip 18.

Referring briefly back to Figure 1, upon removal of the tip 18, the septum 28 resiliently retracts into its closed position.

When the tip 18 is inserted into the connector 10 to the desired depth D, there is a limited amount of annular space between the housing 26 and tip into which portions of the septum 28 may be displaced; however, the septum must be configured and sized to seal before, during and after
5 extension of the penetrating member 12 through the opening 44 to form a closed system.

Referring to Figures 1 and 2, in several applications in the medical environment, it is highly desirable that connectors be configured to seal against a pressure of 20 psi. As noted above, in various connector designs
10 using a pre-slit septum and blunt cannula penetrating member, as described in US Patent no. 5,135,489, incorporated by reference herein, the sealing is accomplished by utilizing a thickened septum and a housing to radially compress the septum thereby sealing a slit extending through the septum. When a blunt cannula of small diameter is forced through the slit, the
15 septum is additionally radially compressed which seals about the cannula, and there appears to be little displacement of portions of the septum in an axial direction.

However, even if a luer tip 18, with its much wider diameter relative to the housing opening than the blunt cannula relative to the corresponding
20 housing opening, could be forced through the slit in such a septum, there is little room in the radial direction to provide a receiving space for the displaced mass of the septum. Thus, the necessary insertion force would likely be too much for most medical practitioners. However, it has been found that thinning the septum 28 to allow displacement and
25 accommodation of the septum between the tip and housing while maintaining the same radial compression does not provide the septum with the ability to seal against a pressure found in fluid passageways i.e. "leak pressure", found during intravenous therapy. Unexpectedly, increasing the radial compression of the thinned septum does not appear to provide a
30 corresponding rate of increase in the leak pressure of the connector 10.

Forming the septum 28 with a thinned upper portion 38 and a downwardly extending lower portion 40 and providing that the opening 44

extends downward through the lower portion 40 in addition to the upper portion 38 greatly increases the leak pressure without requiring a corresponding large increase in septum thickness or compression.

Moreover, tests have shown that the length "L1" (Figure 3) of the lower portion 40 is related to increasing the leak pressure. But, increasing the mass of the septum 28 by increasing the length L1 of the lower portion 40 which must be accommodated within the housing 26 when a luer tip 18 penetrates the resealing member 28, increases the insert force and could possibly prevent the tip 18 from extending entirely through the opening 44.

The first embodiment's configuration of a unique combination with a predetermined length L1 of the lower portion 40, thickness and compression of the upper portion 38 gives the connector 10 a leak pressure of more than 20 p.s.i while presenting an acceptable insert force. Other features of the configuration of the first embodiment is the ability to provide a reseal, after multiple insertions of the luer tip and long periods of luer tip indwell, against a pressure of 6 p.s.i.

As an example, in the first embodiment, forming the septum with the upper portion 38 having a thickness of .040 inches and a 3.5% radial compression or greater and the lower portion 40 having a length L1 of about .080 inches (giving rise to a opening length of .125 inches) yields a connector 10 which may accept the luer tip 18 to the desired depth D while maintain a leak pressure in excess of 20 p.s.i.

Referring in particular to Figures 3 and 3a, preferably the lower portion 38 is formed with a width "W1" of approximately .060 inches and a length "L2" of about .190 inches. The annular skirt 52 is formed with a thickness of about .010 inches. The top surface 70 of the septum 28 is slightly concave to lessen the amount of material being forced into the housing 26 upon insertion of the tip 18 through the opening 44. It is envisioned that the top surface 70 may be flat or have a convex surface or a combination, also. In addition, the top surface 70 is formed unbroken without crevices or other pockets which facilitates disinfecting of the septum 28 with normal aseptic techniques such as swabbing. Also the septum 28 is

formed so that the top surface extends completely over the upper end 30 of the housing to present a visually appealing top surface.

Referring back to Figure 1, to be able to accommodate the standard dimensions of luer fittings, the housing 26 is configured to form a
5 passageway having a diameter "D1" of .235 inches. To facilitate insertion of the septum 28 during assembly, the upper end of the passageway 36 is tapered outward so that a slightly larger diameter of .250 inches is formed at the opening 32

Referring to Figure 2, as can be appreciated, inserting the tip 18 and
10 compressing the upper portion 38 and possibly the lower portion against the annular skirt 52 should produce a thickness layer of at least .050 and .040 inches respectively. However, when inserting one embodiment of a penetrating member 12 having standard luer dimensions to a desired depth D of .300 inches should only provide an annular clearance of .030 inches
15 between the tip and housing 26. Unexpectedly, the elastic material of the septum elongates upon stretching and deforms into this small clearance dimension, while not exhibiting too low a leak pressure after long periods of indwell due to compression set of the septum 28.

Referring again to Figure 3a, the lower portion 40 is formed with
20 rounded corners 74 to form a gap 77 between the lower portion and skirt 52. The rounding of the corners 74 allows the sidewalls 48 and slit 46 to be as long as possible while still providing the gap between the lower portion 40 and skirt 52. Attaching the sidewalls 48 to the skirt 52 without providing a gap may contribute to unequal stretching and deformation of the lower
25 portion 40 about the tip 18 during insertion of the tip resulting in leakage. To create the gap 77 the valve member 27 at the gap 77 has a vertical thickness less than the length L1 of the lower portion. Preferably the gap 77 is formed such that the vertical thickness of the valve member 27 at the gap is equal to the thickness of the upper portion 38 of the septum 28.

30 At the juncture between the central portion 34 and skirt 52 a sharp corner is formed which establishes a hinge point 78. The hinge point 78 which extends about the housing for the entire circumference of the opening

32 also facilitates the flexing and deformation of the septum 28 during insertion of the tip 18.

In an embodiment, the septum 28 is formed of a elastic, resilient material provided by the West Company of Lionville, Pa. It is anticipated
5 that lubricating the septum 28 should facilitate insertion of the luer tip 18. Such lubrication may be applied while forming the slit or by other means such as incorporating the lubrication into the septum material or by applying lubricious coatings to the top surface. In a second embodiment, the
10 septum 28 may be formed of a similar material, such as chlorinated polyisoprene produced by Lexington Medical of Rock Hill, South Carolina. In addition, the slit may be lubricated after assembly of the housing and septum using silicon oil produced by Dow Corning of Midland, Michigan. The housing 26 is rigid and preferably formed of DN003 from Eastar of Kingsport, Tennessee.

15 Although the housing 26 is shown as forming a luer connection 84 at a lower end, the housing may also be formed as a part of any device into which is it desirable to establish a sealed connection such as the injection arm of a Y-site 86 (Figure 7), as an inlet on a stopcock or manifold (not shown) or the like. In addition the lower end of the housing 26 may be
20 integrally formed with a catheter 15 with a guidewire (not shown) extending upward through the opening 44. Referring also to Figure 6, particularly when used as an injection site for a catheter 15, the exterior of the housing 26 is formed with a number of longitudinally extending indentations 86 which facilitate gripping of the connector 10.

25 Referring to Figure 1, to provide for a threaded engagement with a locking flange 20 the upper end 30 of the housing 26 may be formed with a pair of radially extending ears 88 configured to engage the threads 64. Referring to Figure 4, alternately threads 90 may be formed on that portion 92 of the housing 26 which will engage the threads 64 on the flange 20.

30 Preferably the housing 26 is molded as a single piece utilizing molds with a large number of molding cavities to facilitate high speed manufacturing operation. Similarly the valve member 27 is preferably

formed as a single piece in a high speed molding operation, and the shape of the lower portion 40 is particularly suited to register the valve member 27 in a desired orientation for fashioning an opening 44 therein.

Referring to Figures 4-6, a second embodiment of the needleless
5 connector of the present invention is generally indicated at 100 and is particularly suited to a large number of connections and disconnects with a standard male luer lock 13 (Figure 2) without unacceptable leakage. In addition, elements in the second embodiment corresponding to elements in the first embodiment 10 are labeled with the same reference number.

10 The connector 100 includes a housing 102 and an elastic and resilient resealable valve member 104 disposed at an upper end 106 of the housing. The valve member 104 includes the central portion 34 and lower portion 44; however the valve member 104, preferably a septum 105, also includes an annular skirt portion 108 which extends about and surrounds an
15 upper portion 110 of the housing 102 adjacent the upper end 106. Preferably the skirt 108 is bonded to the exterior surface 112 in a specified manner to attach the valve 104 to the housing 102 and elastically restrain the central portion 34 during insertion of the luer tip 18 (Figure 2).

Referring to Figures 4, 5 and 5a, it has been found that the manner in
20 which the valve 104 is configured relative to and attached to the housing 102 has an important effect on the ability of the connector 100 to achieve the desired performance standards. Preferably the valve 104 defines a circular annular receiving channel 118 between the central portion 34 and the skirt 108. The upper end 106 of the housing 102 is received in the
25 channel 118 and bonded to the valve 104 in a desired manner.

The central portion 34 is configured such that the upper edge portion 106 applies a 6 to 7% compression on the central portion. To provide adequate reseal, it is desired that the upper portion 40 of the valve 102 form a thickness of .60 to .50 inches and the lower portion define a length L3 of
30 .080 inches.

Preferably the lower portion 40 is formed with a width "W2" of approximately .060 inches and a length "L4" of about .165 inches. The

annular skirt 108 is formed with a thickness of about .010 inches. The top surface 70 of the septum 28 is slightly concave to lessen the amount of material being forced into the housing 102 upon insertion of the tip 18 (Figure 2) through the opening 44. It is envisioned that the top surface 70 may be flat or have a convex surface or a combination, and is adapted to disinfecting techniques such as swabbing.

At the interface between the central portion 34 and upper end 106 of the housing 102, the valve member 104 forms a sharp corner and thereby forms a hinge point 78. Similar to the first embodiment 10, lower portion 40 is spaced from the housing to form a gap 77.

It has been found that bonding an upper landing 117 defined by an upper edge 116 to the valve 104 and about the entire circumference of the of the upper edge is important in the ability of the connector 100 to maintain a satisfactory leak pressure and increasingly important to maintain the leak pressure after 100 or more connections and disconnects. The bonding also anchors the septum 28 to the upper edge and prevents a rubbing between the septum 28 and upper edge 116 as the septum is elastically stretched during insertion of the tip 18.

Bonding between the exterior surface 112 and the inner surface of the skirt 108 is also important, but migration of any bonding agent to the interface between the central portion 34 and housing 102 should be minimized. If adhesive collects in the interface about the septum 28 and interior surface 119 cracking of the housing 102 or compression set of the septum 28 with corresponding leakage after long periods of indwell may result.

One preferred method of applying bonding agent to the housing 102 such that the upper landing 117 and exterior surface 112 receive such agent while minimizing migration to the interior of the housing is minimized is by placing the housing 102 in a vertical position with the upper edge 116 facing downwards. Bonding agent is applied, preferably by injection, to the exterior surface 112 and gravity causes the agent to flow down and wet the landing 117. Gravity also hinders any migration of the bonding agent into

the interior surface of the housing 102. A further preferred step includes inserting the upper end portion 110 of the housing 102 into a chamber (not shown) and applying a negative air pressure below the housing 102 such that air flows downward along the housing which also hinders migration of the bonding agent upwards into the interior of the housing.

It has been found that a UV curing adhesive, such as Loctite 3011, 3311 and 3301 from Loctite Corporation of Rocky Hill, Connecticut may be utilized as a suitable bonding agent for any of the connectors 10, 100, 200. The bonding agent should be cured for a sufficiently long period of time.

Referring to Figures 4 and 6, to provide for threaded engagement with the locking flange 20, threads 90 extend along a portion of the exterior surface 112. The upper end 127 of the threads 90 are spaced from the upper edge 116 of the housing 102 to form a surface 124 free of threads, ridges or the like to facilitate the bonding of the skirt 108 to the surface 124. In a preferred embodiment the surface 124 is also formed with very little if any draft or taper so that the skirt 108 does not creep upward during setting of the bond between the valve 104 and housing 102. Preferably the skirt 108 extends downward along the housing 124 for a length L5 of about .07 to .08 inches

Referring also to Figure 2, to minimize shredding of a lower edge 126 of the skirt 108 by the threads 64 on the locking flange 20 during removal of the penetrating member 12 it is important that such threads do not catch on the edge 126. Thus it is desired that the lower edge 126 be separated from the upper edge 127 of the threads 90 such that the width of a defined gap 128 is less than the width of the threads 64.

To facilitate a releasable engagement of the penetrating member 12 to the connector 100 and to minimize or eliminate any shredding of the skirt 108, the skirt 108 may be provided with a thickness such that there is minimal interference between the skirt 108 and the inner edge surfaces 64a of the threads 64 on the locking flange 20. However the smaller the diameter defined by the skirt 108 with a given skirt thickness and housing

thickness, the smaller the volume which must accommodate both the penetrating member 12 and valve 104 upon insertion of the member 12.

It has been found that providing a housing 102 with the upper portion 110 having an external diameter of .25 inches and defining an opening 144 with a diameter of .22 is desired to provide the proper clearance between the skirt 108 and locking flange 20 of an ISO standard luer connection and yet also provide a housing with sufficient wall strength to resist fracture and provide sufficient space for the displaced septum 28 and luer tip 18 when the luer tip is inserted into the housing 102.

Referring to Figure 4 in conjunction with Figure 2, the frustoconical shape of an ISO standard luer tip defines a diameter ranging from .155 in. to .175 inches. Thus when an ISO standard luer tip 18 is inserted the desired insertion distance D, it would be expected that the tip and housing 102 define a clearance therebetween of .031 to .021 inches. What is surprising is that upon insertion of a male luer tip 18, the valve 102 having an upper portion 38 with a thickness of about .055 inches extends about the luer tip and is compressed within the smaller clearance without requiring an unacceptable insertion force. In addition, although one may expect some compression set of the septum 28 due to the compression between the tip and housing which would lead to leakage after long indwell problems, it has been unexpectedly found that the valve member 104 maintains an adequate leak pressure after long periods of indwell.

As illustrated in Figure 7, the displacement and compression of the septum 28 into the space between the tip 18 and housing 102 during insertion of the tip substantially fills the space between the lower portion 40 and housing 102 for a depth corresponding to the majority of the extended length of the lower portion about the tip 18. The compressed septum 28 displaces or flushes any fluid that has collected in this space. The injection of the fluid from the tip 18 into the interior of the housing 102 flushes any remaining spaces within the housing. Thus stagnant pockets of fluid are avoided. The filling of the passageway 36 with the tip 18 and displaced septum 104 also reduces priming volume to a low level.

Referring to Figure 7, an embodiment of the needleless connector of the present invention is generally illustrated at 130. In particular the connector 130 is shown as forming part of a Y-site connection assembly 86. As is generally known in the field, Y-site connection assemblies 86 are particularly suited for adding supplemental fluid to a flow of fluid along a primary flow path 132 extending from an upper or entry section 134 of attached tubing, through the Y-site assembly 86 and out along a lower or exit section 136 of attached tubing.

The needleless connector 130 is shown as generally corresponding to the second embodiment of the needleless connector 100, however, the resealable valve member 140 and housing 138 proximate the valve member may be shaped to correspond to the housing and valve member of either the first embodiment 10, second embodiment 100 or the later described embodiment 200.

As can be appreciated, once the luer tip 18 penetrates the valve member 140, the passageway 66 in the tip is placed directly in fluid communication with that portion of the primary flow path 132 extending into the exit section 136 without any intermediate valves so any flow restriction is reduced.

Referring to Figure 8, a third embodiment of the needleless connector of the present invention which is preferred, is generally indicated at 200. The third embodiment 200 has a housing 202 and includes the resealable valve member 104 described in relation to the second embodiment 100. The housing 202 is similar to the first embodiment 100 except that a housing portion 204 below the gap 128 has been altered so that connector 200 provides a higher removal resistance torque. Elements in the third embodiment 100 corresponding to elements in the first or second embodiment 10 are labeled with the same reference number.

In particular, the housing 202 includes the upper portion 110 having the surface 124 of a generally constant outside diameter over which the skirt 108 extends. A middle portion 206 extends downward from the upper portion 116 and a lower portion 208 extends downward from the middle

portion. The lower portion 208 preferably defines a generally constant diameter greater than the diameter defined by the upper portion 116. The middle portion 206 is formed to provide a transition from the upper portion 116 to the relatively wider lower portion 208. Preferably the middle portion 5 206 is frustoconically shaped.

Referring to Figs 2 and 8, the housing 202 defines a set of double start threads 210 which extend downward along the housing about the middle portion 206 and lower portion 208. In the preferred configuration, the threads 210 define a constant major diameter as the threads extend 10 along the lower and middle portions such that the height of the threads decreases as the threads move downward along the middle portion. However the diameter defined by the lower portion 208 is greater than the minor diameter defined by the internal threads 64 on the locking flange 20 such that there is a sliding frictional engagement between the threads 64 15 and middle and lower portions 206, 208. The frictional engagement allows the connector 200 to provide an acceptable removal resistance torque for an attached luer lock when the tip 18 has penetrated to the desired insertion depth D.

Utilization of an upper portion with a surrounding skirt 108 defining a 20 diameter approximately that of the standard major diameter of threads 64, a frustoconical middle portion 206 defining a diameter increasing from a diameter less than the diameter defined by the skirt 108 to the diameter of the lower portion 208 and the lower portion defining a diameter greater than the minor diameter of the internal threads 64 imparts a feel to the user 25 similar to connecting to a standard female luer connection.

When the user first inserts the locking flange 20 over the connector 200, slipping the flange over the upper portion 116 and surrounding skirt 108 promotes centering of the luer tip 18 relative to the connector 200 and minimizes the opportunity for cross threading. As the tip and flange 20 30 continue over the connector 200, the threads 64 then engage the threads 210 and the connector 200 must then be rotated relative to the flange 20 to threadingly engage the flange 20 to the connector 200.

During rotation, the tip 18 extends through the opening 44 and rubs against the valve 104 however such contact supplies very little resistance to turning. The threads 64 engage the middle portion 206 and a sliding frictional engagement begins and the required torque to advance or
5 unthread slowly increases as the tip is rotatably advanced. The threads 64 then engage the lower portion 208 having a constant diameter which slows down the rate or increase in the removal torque before an unacceptable removal torque is achieved which may cause the locking flange 20 to lock up on the connector.

10 In addition male luer locks 13 may be made of many different types of materials which range in stiffness. It is important that the connection of the connector 200 to the luer lock not place such a stress on the locking flange 20 which may fracture the flange. The use of the lower portion 208 with a constant diameter also accommodates luer locks of various materials
15 while preventing overstressing of the locking flange 20.

Thus five example embodiments of a needleless connector have been described. It is believed that the embodiments provide features which solve many of the drawbacks which have hindered widespread acceptance of such needleless connectors relative to the market acceptance of the type
20 of connectors which must be pierced with a sharp needle or blunt cannula.

Referring to Figure 9, an alternate embodiment of the connector uniquely suited to handling higher leak pressures is generally indicated at 300. The connector 300 includes an elastic resealable member 301 such as a septum 302 attached to a housing 304. The septum 302 includes a
25 generally disk shaped upper portion 306 and a generally tubular extension 308 depending downward within a passageway 310 formed by the housing 304. The extension 308 is attached to the housing 304 to form a sealed conduit 314 for the transmission of fluids injected through an opening 316, preferably a slit 318, extending through the upper portion 306.

30 Referring briefly to Figure 1 also, in a manner similar to the septum 28, the opening 316 may extend partially through the septum 302 with the anticipation that the opening will extend completely through the septum

upon penetration by the luer tip 18. In addition, the upper portion 306 may be formed in a manner similar to the upper portion 38 of septum 28.

A valve element, generally indicated at 320, provides at least one seal against pressurized fluid within an exit passageway 324 formed by portions of the extension 308 and housing 304. The exit passageway 324 is in fluid communication with a device 326 in fluid communication with a body. The device 326 may include a catheter or an I.V. administration set. If the connector 300 is for providing a resealable connection with an I.V. administration set, the housing 304 will preferably form a portion of a Y-site.

The valve 320 includes a pincher portion 328 which pinchingly deforms the extension 308 to seal against leak pressure found in the exit passageway 324. The pincher portion 328 is attached to the housing 304 by fixedly clamping a peripheral edge 330 between an upper housing piece 334 and a lower housing piece 336 which are bonded together to form the housing 304.

The connector 300 also includes an extension collapsing element 338 which contacts and partially collapses a portion of the extension 308 after and possibly during the sealing of the extension by the valve 320. The partial collapsing produces an expelling of fluid from the exit passageway 324 after the sealing of the extension by the valve 320.

Referring also to Figure 5, in the preferred embodiment, the collapsing element 338 is connected to, by being integrally formed as a portion of, the valve 320. The collapsing element 338 includes two legs 340 connected to and extending downward and outward from the pincher portion 328. The legs 340 extend on opposite sides of the extension 338 and contact the extension deforming the extension radially inward. When a luer tip 18 penetrates the septum 302 by extending through the opening 316, to the desired depth D, the tip contacts the pincher portion 328 displacing it downward and opening the element to place the passageway 66 in fluid communication with the exit passageway 324. The legs 340 are also forced radially outward against the housing 304 allowing the extension 308 to expand. During removal of the tip 18, the pincher portion 328 of the

valve 320 closes, initially sealing the extension 308, and then the legs 340 continue to collapse the extension 308 below the pincher portion forcing a portion of the fluid out of the exit passageway 324 into the device 326.

To place the pincher portion 328 in a better position for contact and activation by the luer tip 18, the valve 320 may be formed with a central portion 344 offset upward of the peripheral edge 330. The legs 340 are attached to this central portion 344; however, the legs may be attached to other parts of the housing 304.

To facilitate sealingly attaching the extension 308 to the housing 306, the lower piece 336 forms a radial lip 346, and the lower end of the extension is adhesively attached to the housing 305 proximate this lip. To hinder buckling of the extension 308 when the luer tip 18 forces the central part of the septum 302 downward, the extension may be stretched during assembly and attached to the housing in the stretched configuration.

Referring briefly to Figures 1 and 4, in a manner similar to the connector 10, the septum 302 of the connector 300 may include an annular skirt 348 and radial lip 350 which are bonded to the housing 304.

The attachment of the extension 308 to the upper portion 306 of the septum 302 and the housing 304 may help support the upper portion 306 against leaking due to pressurized fluid in the conduit 314. The extension 308 also prevents fluids from flowing into the housing outside of the extension an into areas which may be difficult to flush during use of the connector 300.

The septum 302 may also include a lower portion (not shown) similar to lower portion 40 (Figure 3), but preferably the valve 320 provides most of the seal against leakage due to the pressure of fluid in the exit passageway 324.

Referring to Figures 11 and 12, a further alternate embodiment of a connector uniquely suited to providing a flow of fluid into the device 326 after removal of the tip 18 is generally indicated at 200. Referring also to Figure 1, the connector 200 includes a resealable member 201, preferably a septum 202 having an upper portion 204 similar in construction to upper

portion 38, an annular skirt 206 similar in construction to the annular skirt 52, and a lower portion 208 and opening 210 similar in construction to the lower portion 40 and opening 44, respectively. The lower portion 208 is shown having a V shaped cross section; however, other configurations such as the configuration of lower portion 40 are also acceptable.

The septum 202 is attached to the top end 212 of housing 214 to seal an opening 216 formed by the top end. The housing forms an internal chamber 218 and a radially extending valve seat 220. A lower end 224 of the housing 214 is adapted to form a luer connection with the device 326 which is adapted to be placed in fluid communication with the body.

The septum 202 also includes a downward depending generally tubular extension 228 which extends to a point in reasonably close proximity with the valve seat 220. Sealingly attached to a lower end 230 of the extension 228 is a radial sealing flange 234. The flange 234 extends radially outward and forms a peripheral edge 236 which sealingly attaches to the housing 214. The septum 202 and flange 234 cooperate to prevent fluid flowing through a passageway 238 formed within the extension 228 from flowing into the chamber 218 outside of the extension and between the flange 234 and top end 240 of the housing.

Disposed within the housing 214 and about an outlet 240 of the chamber 218 is a valve 248. The valve 248 is uniquely configured to provide less fluid flow resistance when low pressure fluid is within the passageway 238 and high fluid flow resistance when high pressure fluid is within the passageway. Referring to Figures 6 and 7, the valve includes a radial sealing flange 250 having a peripheral portion 254 extending over the valve seat 220.

The valve 248 includes a set of downward depending legs 256 which contact a radial ledge 258 formed by the housing 214. The legs 256 are configured to support the flange 250 so that the peripheral edge 236 is spaced from the valve seat 220. Thus fluid may flow from the passageway 238 around the peripheral edge 254 and out an outlet 260 for the connector 200. The legs 256 are also configured to flex when fluid over a certain

pressure is injected through the opening 210 and into the passageway 238 (as particularly illustrated in Figure 12), the pressure of the fluid and the action of the fluid flowing around the peripheral portion 254 flexes the legs 256 and the flange 250 moves downward to seal against the valve seat 220.

5 The valve 248 also includes a capillary tube 262, preferably of a small diameter and constructed of metal, glass or the like, which extends through the flange 250 to form a passageway for a small flow of fluid from the passageway 238 into the outlet 260. The tube 262 is preferably sized so that the flow of fluid through the passageway is enough to maintain a
10 KVO or keep vein open flow of fluid to the device 326.

 Also when the luer tip 18 is inserted through the opening 210 and fluid is injected into the extension 228, the extension elastically expands in a radial direction to form a reservoir 268. The resiliency of the extension 228 maintains the fluid at a pressure sufficient to keep the flange 250 sealed
15 against the seat 220 so that fluid only flows through the capillary tube 262. When sufficient fluid flows out of the reservoir 268 so that the extension 228 is in an almost deflated configuration, the pressure of the fluid in the passageway 238 drops to a level whereby the legs 256 straighten and the flange 250 separates from the valve seat 220 to allow much greater flow
20 into the outlet 260.

 Therefore it may be seen that by varying the configuration and material of the legs 256 in conjunction with the material of the extension 228, the pressure at which the valve 248 opens may be altered.

 Referring to Figure 13 a further alternate embodiment of the
25 needleless connector is generally indicated at 400. The connector 400 includes an elastic, resilient, resealable valve 402 having an upper portion 404, middle portion 406 and annular skirt 408 similar in configuration to the upper portion 38, lower portion 40 and annular skirt 108, respectively of connector 200 (Figure 8). In addition the valve 402 includes a conically
30 shaped tubular lower portion 410 integrally attached to the middle portion 406 such that an opening 414, preferably a slit, extends downward through

the upper portion 404 and middle portion 404 into a chamber 416 defined in part by the lower portion 410.

A lower edge 417 of the lower portion 410 is sealingly engaged to a housing 418, preferably rigid, of the connector 400. In particular the housing 418 includes an upper portion 420 similar in configuration to the upper end of connector (Figure 8) to supply the desired removal torque resistance capabilities. The housing also includes a lower portion 424 having a lower end 426 configured to establish a connection to a medical device (not shown) such as a catheter 15 (Figure 1).

The lower edge 417 of the lower portion 410 extends about and is attached to an upwardly extending nipple 428. A collar 430 formed by the lower portion 424 of the housing 418 extends about the lower edge 417 and clamps the lower edge to the nipple 428. The lower portion 424 and upper portion 420 are attached to each other preferably by sonic welding or other appropriate type.

Referring to Figures 13 and 14, the connector 400 is particularly suited to eliminating voids and minimizing priming volume as the flow path is within the lower portion 410 of the valve 402 and fluid cannot flow into the space between the valve and upper housing. In addition, by appropriately dimensioning the valve 402, the chamber 416 defined by the lower portion 410 when no luer tip 18 is inserted into the connector 400, defines a volume which is less than the chamber 416' defined by the lower portion 410 when the luer tip is inserted. Thus siphoning of fluid into the chamber 416 upon removal of the tip 18 is avoided. Instead a slight flow of fluid from the chamber 416' through the lower end of the valve 426 upon removal of the tip 18 may occur.

Referring to Figure 15 and 16 a needleless connector particularly suited to preventing siphoning upon removal of a luer tip 18 is generally indicated at 450. Preferably the connector 450 is similar to the connector 400 (Figure 13) and elements in the connector 450 corresponding to elements in the connector 400 are labeled with the same reference number.

However connector 450 also includes a collapsing member 452, preferably a split collar 454 which is disposed in the void 456 between the lower portion 410 of the valve 402 and the upper portion 420 of the housing 418. The collapsing member 452 includes opposing inward landings 458 disposed on opposite sides of the lower portion 410 and engaging the lower portion to collapse the lower portion thereby lowering the volume of a chamber 460 defined by the lower portion. The landings 458 are resiliently supported by legs 464 angled in an outward direction. The collapsing member 452 may be composed of metal or other material which provides the desired resiliency in the legs 464.

Upon insertion of the luer tip 18, the luer tip 18 forces the landings 458 outward, bending the legs 464 so that the legs become generally aligned with the landings 458 and the lower portion 410 below the tip 18 defines the chamber 460'. Fluid may then be injected into the connector. Upon removal of the tip 18, the resiliency of the lower portion 410 will cause the lower portion to seek to assume the conical shape; however, the legs 464 will force the landings 458 inward to further collapse the lower portion such that the chamber 460 defined by the lower portion has a smaller volume than chamber 460'. Thus siphoning of fluid into the chamber 460 upon removal of the tip 18 is avoided and a slight volume of fluid is expelled from the chamber 460' through the lower end 426 upon the tip removal.

It will be understood that the embodiments of the present invention which have been described are illustrative of some of the applications of the principles of the present invention. Various modifications may be made by those skilled in the art without departing from the true spirit and scope of the invention.

What is claimed is

1. A connector device for establishing a sealed connection with a male luer tip comprising:
 - a housing forming a distal end opening and a central passageway
 - 5 sized to receive the male luer tip, said passageway extending from said opening in a proximate direction;
 - a resealable valve resiliently restrained relative to said housing, said valve including a first radial portion sealingly extending about said opening and a second portion integral with said first portion and extending within
 - 10 said passageway from a proximate surface of said radial portion, and a third portion attached to and extending proximally from said second portion, a portion of said third portion being spaced from said housing whereby insertion of the tip displaces such spaced portion and a lower portion of said third portion attached to said housing; and
 - 15 an opening formed in said valve such that when the luer tip is inserted through said septum said first portion and said second portion elastically extend about the luer tip. whereby said valve seals against a fluid within said passageway.
2. The connector device of claim 1 wherein said valve includes a septum having an annular skirt attached to said first portion, said skirt extending over and attached to an outside surface of said housing proximate said opening.
3. The connector device of claim 2 wherein said septum includes an annular channel formed by said skirt and said first portion, a distal edge portion of said housing received in said channel.
4. The connector device of claim 3 wherein said distal edge portion forms a distal landing received in said channel, at least a portion of said distal landing being attached to said septum.

5. The connector of claim 4 wherein the entire length of said landing is attached to said septum.
6. The connector device of claim 4 wherein said connector includes a bonding agent to attach said outside surface and said landing to said septum.
7. The connector device of claim 6 wherein said connector includes an amount of said bonding agent attaching said first portion to said housing being equal to or less than the amount of bonding agent found on an inside surface of said housing at said distal edge portion when said bonding agent is applied to said outside surface when said housing is oriented with said distal edge portion in a downward direction..
8. The connector device of claim 1 wherein said second portion of said resealable valve is formed with a generally rectangular cross section in the proximate direction.
9. The connector of claim 1 wherein the male luer tip is encircled by an annular locking flange and said housing includes a distal edge portion having an outside surface of generally constant diameter, and a second portion extending proximally from said edge portion and having a generally frustoconical shape, said second portion being threaded for threadingly engaging the locking flange.
10. The connector device of claim 9 wherein the valve includes an annular skirt attached to said first portion, said skirt extending over and attached to said outside surface of said distal edge portion.

11. A connector device for establishing a sealed connection with a male luer lock including a male luer tip encircled by an annular locking flange, said device comprising:

5 a housing forming a distal end opening and a central passageway sized to receive the male luer tip, said passageway extending from said opening in a proximate direction, said housing including a first distal edge portion having an outside surface of generally constant first diameter, and a second portion spaced from said distal edge portion and having an outside surface of a generally constant second diameter, said second diameter
10 being larger than said first diameter, said housing including a third portion extending from said distal edge portion to said second portion, said third portion having an outside surface with a changing diameter;

a resealable valve resiliently restrained relative to said housing, said valve including a first radial portion sealingly extending about said opening
15 and a second portion integral with said first portion and extending within said passageway from a proximate surface of said radial portion, said valve having a third portion attached to said second portion and configured to expand in an outward direction upon insertion of the luer tip, and a lower end of said third portion attached to said housing; and

20 an opening formed in said valve such that when the luer tip is inserted through said septum said first portion and said second portion elastically extend about the luer tip whereby said valve seals against a fluid within said passageway.

12. A connector device for establishing a sealed connection with a male luer tip comprising:


5 a housing forming a distal end opening and a central passageway sized to receive the male luer tip, said passageway extending from said opening in a proximate direction;

a resealable valve resiliently restrained relative to said housing, said valve including a first radial portion sealingly extending about said opening and a second portion integral with said first portion and extending within

said passageway from a proximate surface of said radial portion, , said
10 valve having a third portion attached to said second portion and configured
to expand in an outward direction upon insertion of the luer tip, and a lower
end of said third portion attached to said housing;

an opening formed in said valve such that when the luer tip is
inserted through said septum, said first portion and said second portion
15 elastically extend about the luer tip whereby said valve seals against a fluid
within said passageway; and

a low flow valve disposed generally within the third portion of said
valve.



2/14




FIG. 2

3/14




FIG. 3




FIG. 3A

4 / 14




FIG. 4

5/14




FIG. 5




FIG. 5A

6 / 14




FIG. 6

7/14




FIG. 7

8/14






FIG. 8

9 / 14

FIG. 9




10/14




11 / 14

FIG. 11



12 / 14

FIG. 12



13/14




FIG. 13




FIG. 14




FIG. 15





FIG. 16



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 39/04	A3	(11) International Publication Number: WO 99/59672 (43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/US99/11146 (22) International Filing Date: 20 May 1999 (20.05.99) (30) Priority Data: 09/081,728 20 May 1998 (20.05.98) US (71) Applicant: BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US). (72) Inventors: JEPSON, Steven, C.; 103 S. Cedar Street, Palatine, IL 60067 (US). DUDAR, Thomas, E.; 228 North Crescent, Palatine, IL 60067 (US). MONTANEZ, Rodrigo, A.; Apartment 1514, 1390 South White Oak Drive, Waukegan, IL 60085 (US). BINDOKAS, Algirdas, J.; 67 Waverly, Clarendon Hills, IL 60514 (US). FINLEY, Michael, J.; 30617 East 113th Street, Wilmot, WI 53192-0084 (US). WHITE, Jason, J.; 7936 South Calumet, Chicago, IL 60619 (US). SUMMERS, Camille; 39963 N. Hidden Bunker Court, Antioch, IL 60002 (US). DING, Y., Samuel; 302 Richmond Lane, Vernon Hills, IL 60061 (US). DANIELS, Lewis, E.; 5018 W. Lake Shore Drive, Wonder Lake, IL 60097 (US). (74) Agents: NICHOLS, Jeffrey, C. et al.; Baxter International Inc., One Baxter Parkway, Deerfield, IL 60015 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 2 March 2000 (02.03.00)
(54) Title: NEEDLELESS CONNECTOR (57) Abstract A needleless connector (450) is provided which utilizes a resealable preslit septum valve (402). The valve (402) is resiliently restrained relative to a housing (418) with the valve and housing configured to accept a standard male luer lock having a luer tip (18) which penetrates the valve through the opening to extend within the housing and a luer locking flange of the luer lock extending about the housing. The valve (402) includes a disk shaped upper portion (404) covering the opening, a lower portion (406) spaced from the housing (418) and extending downward from the disk shaped portion into a passageway defined by the housing (418), and an annular skirt (408) to attach the septum to the housing. The connector (450) exhibits satisfactory leak pressure after multiple connections and disconnects to the luer lock fitting and long periods of indwell of the luer tip (18).		



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	JP	Japan	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	KE	Kenya	NL	Netherlands	VN	Viet Nam
CG	Congo	KG	Kyrgyzstan	NO	Norway	YU	Yugoslavia
CH	Switzerland	KP	Democratic People's Republic of Korea	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KR	Republic of Korea	PL	Poland		
CM	Cameroon	KZ	Kazakhstan	PT	Portugal		
CN	China	LC	Saint Lucia	RO	Romania		
CU	Cuba	LJ	Liechtenstein	RU	Russian Federation		
CZ	Czech Republic	LK	Sri Lanka	SD	Sudan		
DE	Germany	LR	Liberia	SE	Sweden		
DK	Denmark			SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/11146

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61M39/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 470 319 A (MAYER BRUNO F P) 28 November 1995 (1995-11-28)	1-5
A	column 9, line 59 -column 14, line 42; figures 6-10	6
A	--- WO 94 15665 A (MEDEX INC) 21 July 1994 (1994-07-21) page 9, line 17 -page 10, line 18; figure 3	1
A	--- US 4 261 357 A (KONTOS STAVROS B) 14 April 1981 (1981-04-14) column 3, line 29 - line 51; figure 2 -----	6,7

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

24 September 1999

Date of mailing of the international search report

10 January 2000 (10.01.00)

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Levert, C

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 99/ 11146

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

- ☐ Only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1,2-7

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1. Claims: 1,2-7

Connector device with a valve including a septum, which is attached to an outside surface of the housing by a bonding agent. (searched)

2. Claims: 1,8

Connector device with a resealable valve having a portion formed with a generally rectangular cross section in the proximate direction. (not searched)

3. Claims: 1,9-10; 11

Connector device with an outside surface of generally constant diameter at the distal edge portion and of a generally frustoconical shape at the second portion, which is threaded. (not searched)

4. Claim : 12

Connector device with a low flow valve disposed generally within a portion of a resealable valve. (not searched)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/11146

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5470319 A	28-11-1995	AU 2776795 A	15-01-1996
		CA 2193232 A	28-12-1995
		EP 0901389 A	17-03-1999
		US 5971965 A	26-10-1999
		WO 9535125 A	28-12-1995
		US 5616129 A	01-04-1997
		US 5616130 A	01-04-1997
		US 5788675 A	04-08-1998
		US 5820601 A	13-10-1998
		US 5836923 A	17-11-1998
-----	-----	-----	-----
WO 9415665 A	21-07-1994	AU 6087394 A	15-08-1994
		US 5417673 A	23-05-1995
-----	-----	-----	-----
US 4261357 A	14-04-1981	AU 530522 B	21-07-1983
		AU 5499580 A	07-08-1980
		CA 1121682 A	13-04-1982
		DE 3002915 A	31-07-1980
		DK 35680 A	30-07-1980
		FI 800239 A	30-07-1980
		FR 2447201 A	22-08-1980
		GB 2044106 A,B	15-10-1980
		IE 49068 B	24-07-1985
		IT 1128094 B	28-05-1986
		NZ 192581 A	19-11-1981
		SE 8000638 A	30-07-1980
		ZA 8000479 A	30-09-1981
-----	-----	-----	-----